

## **SK 1150**Wet Blasting Machine





Standard Features	Explanation	
• Wet Blasting Cabinet Air Suction Fan	1.1 Kwh / 3000 Rpm Fan Motor with High Suction Power	
• Sandblasting Cabinet	One Gate - Laser Cut - 1100x900x800 (h)mm Dimension. All parts contacted to water and sand mixture are stainless steel.	
Elektrical Panel	Motor Protected. Air Pressure, Sand Injection and Phase Gauge	
Sandblasting Nozzle	Boron Carbide Nozzle, 1500 Hours Operation Guarantee	
Sandblasting Gun	Stainless Steel Body, 1,2 m3/min Sand-Air Mixture Blasting at 6 Bar. Custom Made Injector	
• Lighting	2x18 watt Led Light	
• Foot Pedal	Foot Protected Double Exit	
Regulator	Adjustable Sandblasting Pressure	
Sandblasting Glove	24" 1. Quality Rubber, Knurled Pattern	
• Sight Glass	Panaromic	
Sandblasting System	Injection Sandblasting System, Adjustable Blasting Amount (Maximum control with pressure and sand feed regulator)	
Electrostatic Paint	Ral 7035	
Sand And Water Amount Gauge	Gauges at Cabinet Chamber	
Gun Stabilization	Ability To Operate With Two Hands	
Cabinet Safety Package	Gate Switches, Solenoid Valve and Custom Made Panel	
PLC Controlled, Touch-screen and	TFT 7" Screen, 3,5 kWh Resistant	
• Electrical Sight Glass Wiper Water Heating System	Provides High Visibility While Blasting	
• Conveyor	Roll Type / 300 mm width - 3000mm length	

SANDBLASTING ABRASIVES USED IN SK 1150 WET BLASTING CABINET			
TYPE	GRAIN FEATURES	PURPOSE OF USE	
Aluminum Oxide	Hard, Angular	Roughening, Paint Removal	
Glass Bead	Hard, Spherical	Finishing, Polishing	
Garnet	Hard, Angular, Economic	Roughening, Paint Removal	
Silicon Carbide	Hard, Angular	Roughening, Paint Removal	
Ceramic Bead	Hard, Spherical	Finishing, Polishing	
Plastic Abrasive	Soft, Angular	Precision Blasting	

Ferhatpaşa Mahallesi Mareşal Fevzi Çakmak Cad. No: 78/C Ataşehir İstanbul Telefon: 0216 660 14 80 Fax: 0216 660 14 81





METALURJİ VE YÜZEY İŞLEM ÜRÜNLERİ NAK. TUR. SAN. TİC. ve LTD. ŞTİ.